






Part No. 809212
SIBERIA NG WARNING LIGHT LED BAR 20"



Part No. 809213
SIBERIA NG WARNING LIGHT LED BAR 32"



Part No. 809214
SIBERIA NG WARNING LIGHT LED BAR 38"



SIBERIA NG WARNING LIGHT LED BAR

E-APPROVED / DUAL POSITION LIGHT / UNIQUE STROBE FUNCTION



PART NO.	809212	809213	809214
VOLTAGE	9-35V DC	9-35V DC	9-35V DC
CONSUMPTION	54W	87W	108W
THEORETICAL LUMEN	7560	12 000	14 400
ACTUAL LUMEN	2467	4979	5867
1 LUX @	414 m	436m	452m
IP-CLASS	IP67/IP69K	IP67/IP69K	IP67/IP69K
BEAM PATTERN	Combo	Combo	Combo
POSITION LIGHT	White and amber	White and amber	White and amber
CONNECTION	Cable	Cable	Cable
CABLE LENGTH	2500 mm	2500 mm	2500 mm
MATERIAL HOUSING	Aluminium	Aluminium	Aluminium
MATERIAL LENS	Polycarbonate	Polycarbonate	Polycarbonate
LENGTH	504,6 mm	810,6 mm	963,6 mm
DEPTH	55,5 mm	55,5 mm	55,5 mm
HEIGHT	45 mm	45 mm	45 mm
HEIGHT INCLUDING BRACKET	65 mm	65 mm	65 mm
OPERATING TEMPERATURE	-20°C · +45°C	-20°C · +45°C	-20°C · +45°C
E-APPROVED	ECE R7, R65, R112	ECE R112, R7, R65	ECE R112, R7, R65
REF	45	45	45
EMC-CERTIFICATE	ECE R10	ECE R10	ECE R10